

Vulcan Pack

Metal decorating



Vulcan Pack



Main Application

Metal decorating

Advantages of the product

- > Suitable for conventional/UV inks
- > Ideal for 4-colour presses
- > Excellent half tone reproduction and ink transfer coverage
- > High edge marking resistance

Vulcan Pack is available in 3ply, 1,95 mm thickness



Guiding Value

		Standard	
Color:	Blue		
Structure:	3 ply		
Surface Roughness Ra*:	1,1 micron	IO LAB TEC 060 - E (internal)	
Compressibility @ 0,23 mm*:	3,8 MPa	IO LAB TEC 060 - B (internal)	
Thickness +/-0,02 mm*:	1,95 mm	IO LAB TEC 060 - C (internal)	

^{*} Average value obtained in accordance with the given standard. Please note that the number of samples tested may differ.



Continental Coated Systems Italy S.p.A Strada Provinciale 140, 26855 Lodi Vecchio, Italy www.continental-industry.com/printing-technology The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright @ 2024 Contifech Deutschland GmbH, Hannover, All rights reserved. For complete information go to: www.continental-industry.com/discl_en

