

Vulcan Folio Black
Commercial Sheetfed/Packaging

Vulcan Folio Black




Main Application

Commercial Sheetfed/Packaging

Advantages of the product

- › Suitable for alternating printing (conventional and UV inks)
- › High chemical resistant top surface
- › Very good dot gain reproduction

Vulcan Folio Black is available in 3ply, 1,95 mm thickness



Guiding Value

Standard

Color:	Black	
Structure:	3 ply	
Surface Roughness Ra*:	0,6 micron	IO LAB TEC 060 - E (internal)
Compressibility @ 0,23 mm*:	2,6 MPa	IO LAB TEC 060 - B (internal)
Thickness +/-0,02 mm*:	1,95 mm	IO LAB TEC 060 - C (internal)

* Average value obtained in accordance with the given standard. Please note that the number of samples tested may differ.



Continental Coated Systems Italy S.p.A
 Strada Provinciale 140,
 26855 Lodi Vecchio, Italy
www.continental-industry.com/printing-technology

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2024 ContiTech Deutschland GmbH, Hannover. All rights reserved. For complete information go to: www.continental-industry.com/discl_en