

Rollin NL

Commercial Sheetfed

Rollin NL



Main Application
Commercial Sheetfed

Rollin NL is available in
3ply, 1,95 mm thickness

Advantages of the product

- › Suitable for conventional inks
- › Good print quality for several jobs
- › Available for APAC market



Guiding Value

Standard

Color:	Blue	
Structure:	3 ply	
Surface Roughness Ra*:	0,8 micron	IO LAB TEC 060 - E (internal)
Compressibility @ 0,23mm*:	2,8 MPa	IO LAB TEC 060 - B (internal)
Thickness +/- 0,02 mm*:	1,95 mm	IO LAB TEC 060 - C (internal)

* Average value obtained in accordance with the given standard. Please note that the number of samples tested may differ.



Continental Coated Systems Italy S.p.A
Strada Provinciale 140,
26855 Lodi Vecchio, Italy
www.continental-industry.com/Offsetdrucktücher

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2024 ContiTech AG, Hanover. All rights reserved. For complete information go to: www.continental-industry.com/disci_en

Der Inhalt dieser Druckschrift ist unverbindlich und dient ausschließlich Informationszwecken. Für weitere Informationen besuchen Sie bitte: www.continental-industry.com/disci_de