

## **Printec 815**

Metal decorating

# Printec 815



**Main Application**  
Metal decorating

**Printec 815 is available in**  
**3ply, 1,95 mm thickness**

**Advantages of the product**

- › Suitable for conventional/UV inks
- › Ideal for 4-colour presses
- › Excellent half tone reproduction and ink transfer coverage
- › High edge marking resistance



**Guiding Value**

		Standard
<b>Color:</b>	Blue	
<b>Structure:</b>	3 ply	
<b>Surface Roughness Ra*:</b>	1,1 micron	IO LAB TEC 060 - E (internal)
<b>Compressibility @ 0,23 mm*:</b>	3,8 MPa	IO LAB TEC 060 - B (internal)
<b>Thickness +/-0,02 mm*:</b>	1,95 mm	IO LAB TEC 060 - C (internal)

\* Average value obtained in accordance with the given standard. Please note that the number of samples tested may differ.

 **Continental Coated Systems Italy S.p.A**  
Strada Provinciale 140,  
26855 Lodi Vecchio, Italy  
[www.continental-industry.com/printing-technology](http://www.continental-industry.com/printing-technology)

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2024 ContiTech Deutschland GmbH, Hannover. All rights reserved. For complete information go to: [www.continental-industry.com/disc\\_en](http://www.continental-industry.com/disc_en)