

**Vulcan X-Coat Pro**  
Coating

# Vulcan X-Coat Pro



**Main Application**  
Coating

**Vulcan X-Coat Pro is available in  
1,15 - 1,35 mm thickness**

**Advantages of the product**

- › Polymer coating plate with excellent resistance to UV and Aqueous coatings
- › Excellent dimensional stability thanks to the polyester carrier
- › Very good stripping with clear and visible cut lines
- › Usable in both directions thanks to its fabricless design



**Guiding Value**

**Standard**

<b>Color:</b>	Grey	
<b>Structure:</b>	Fabricless	
<b>Surface Roughness Ra*:</b>	0,6 micron	IO LAB TEC 060 - E (internal)
<b>Compressibility @ 0,23 mm*:</b>	N/A	IO LAB TEC 060 - B (internal)
<b>Thickness +/-0,05 mm*:</b>	1,15 - 1,35 mm	IO LAB TEC 060 - C (internal)
<b>Cutting depth*:</b>	0,8 - 1,0 mm	IO LAB TEC 060 - C (internal)

\* Average value obtained in accordance with the given standard. Please note that the number of samples tested may differ.



**Continental Coated Systems Italy S.p.A**  
Strada Provinciale 140,  
26855 Lodi Vecchio, Italy  
[www.continental-industry.com/printing-technology](http://www.continental-industry.com/printing-technology)

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2024 ContiTech Deutschland GmbH, Hannover. All rights reserved. For complete information go to: [www.continental-industry.com/disc\\_en](http://www.continental-industry.com/disc_en)