



# Sava Advantage UV Red Commercial Sheetfed



## Sava Advantage UV Red



#### **Main Application**

Commercial Sheetfed

#### Advantages of the product

- > Specific for UV inks
- Cord carcass offers excellent smash resistance, rapid recovery and dimensional stability
- > Optimal ink transfer

Sava Advantage UV Red is available in 3ply, 1,95 mm thickness



### **Guiding Value**

		Standard	
Color:	Red		
Structure:	3 ply		
Surface Roughness Ra*:	0,7 micron	IO LAB TEC 060 - E (internal)	
Compressibility @ 0,23 mm*:	2,6 MPa	IO LAB TEC 060 - B (internal)	
Thickness +/-0,02 mm*:	1,95 mm	IO LAB TEC 060 - C (internal)	

\* Average value obtained in accordance with the given standard. Please note that the number of samples tested may differ.



**Continental Coated Systems Italy S.p.A** Strada Provinciale 140, 26855 Lodi Vecchio, Italy www.continental-industry.com/Offsetdrucktücher

**Ontinental** 

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright @ 2024 Contilech Deutschland GmbH, Hannover. All rights reserved. For complete information go to: www.continental-industry.com/discl\_en