

Printec 40

Commercial Sheetfed/Packaging

Printec 40




Main Application

Commercial Sheetfed/Packaging

Advantages of the product

- › Suitable for UV and conventional inks
- › Very good half tone reproduction and overall print quality

Printec 40 is available in 3ply, 1,95 mm thickness



Guiding Value

		Standard
Color:	Light Blue	
Structure:	3 ply	
Surface Roughness Ra*:	0,8 micron	IO LAB TEC 060 - E (internal)
Compressibility @ 0,23mm*:	2,6 MPa	IO LAB TEC 060 - B (internal)
Thickness +/- 0,02 mm*:	1,95 mm	IO LAB TEC 060 - C (internal)

* Average value obtained in accordance with the given standard. Please note that the number of samples tested may differ.



Continental Coated Systems Italy S.p.A
 Strada Provinciale 140,
 26855 Lodi Vecchio, Italy
www.continental-industry.com/Offsetdrucktücher

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2024 ContiTech AG, Hanover. All rights reserved. For complete information go to: www.continental-industry.com/disci_en

Der Inhalt dieser Druckschrift ist unverbindlich und dient ausschließlich Informationszwecken. Für weitere Informationen besuchen Sie bitte: www.continental-industry.com/disci_de