

Rollin Wish

Commercial Sheetfed



Rollin Wish




Main Application

Commercial Sheetfed

Advantages of the product

- > Suitable for UV and conventional inks
- > Very robust and stable carcass
- Good reboundability and striking absorption

Rollin Wish is available in 4ply, 1,95 mm thickness



Guiding Value

		Standard	
Color:	Light Blue		
Structure:	4 ply		
Surface Roughness Ra*:	0,8 micron	IO LAB TEC 060 - E (internal)	
Compressibility @ 0,23mm*:	2,6 MPa	IO LAB TEC 060 - B (internal)	
Thickness +/- 0,02 mm*:	1,95 mm	IO LAB TEC 060 - C (internal)	

^{*} Average value obtained in accordance with the given standard. Please note that the number of samples tested may differ.



Continental Coated Systems Italy S.p.A Strada Provinciale 140, 26855 Lodi Vecchio, Italy www.continental-industry.com/Offsetdrucktücher The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2024 Contifien AG. Hanover. All rights reserved. For complete information go to: www.continental-industry.com/discl_en

Der Inhalt dieser Druckschrift ist unverbindlich und dient ausschließlich Informationszwecken. Für weitere Information besuchen Sie bitte: www.continental-industry.com/discl_de

