



Vulcan Zenith Commercial Sheetfed



Vulcan Zenith



Main Application

Commercial Sheetfed

Advantages of the product

- > Blanket suitable for both conventional and UV inks
- > Good print quality for several jobs

Vulcan Zenith is available in 3ply, 1,95 mm thickness



Guiding Value

| | | Standard | |
|-----------------------------|------------|-------------------------------|--|
| Color: | Blue | | |
| Structure: | 3 ply | | |
| Surface Roughness Ra*: | 0,8 micron | IO LAB TEC 060 - E (internal) | |
| Compressibility @ 0,23 mm*: | 2,8 MPa | IO LAB TEC 060 - B (internal) | |
| Thickness +/-0,02 mm*: | 1,95 mm | IO LAB TEC 060 - C (internal) | |

* Average value obtained in accordance with the given standard. Please note that the number of samples tested may differ.



Continental Coated Systems Italy S.p.A Strada Provinciale 140, 26855 Lodi Vecchio, Italy www.continental-industry.com/printing-technology



The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright @ 2024 Contifect Deutschland GmbH, Hannover, All rights reserved. For complete information go to: www.continental-industry.com/discl_en