

Continental 
The Future in Motion

Sava 

Sava Strip 4 Dual
Coating

Sava Strip 4 Dual



Main Application
Coating

Advantages of the product

- › Rubber coating plate suitable for Aqueous/UV varnishing
- › Excellent dimensional stability thanks to the polyester carrier
- › Easy to strip from polyester base
- › Usable in both directions thanks to its fabricless design


Sava Strip 4 Dual is available in fabricless, 1,15/1,35/1,95 mm thickness



Guiding Value

		Standard
Color:	Grey	
Structure:	Fabricless	
Surface Roughness Ra*:	0,6 micron	IO LAB TEC 060 - E (internal)
Compressibility @ 0,23 mm*:	N/A	IO LAB TEC 060 - B (internal)
Thickness +/-0,02 mm*:	1,15/1,35/1,95 mm	IO LAB TEC 060 - C (internal)
Cutting depth*:	0,8/1,0/1,0 mm	IO LAB TEC 060 - C (internal)

* Average value obtained in accordance with the given standard. Please note that the number of samples tested may differ.

 **Continental Coated Systems Italy S.p.A**
Strada Provinciale 140,
26855 Lodi Vecchio, Italy
www.continental-industry.com/Offsetdrucktücher

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2024 ContiTech Deutschland GmbH, Hannover. All rights reserved. For complete information go to: www.continental-industry.com/discl_en