



## PAGUCLAMP

The ideal half-shell fitting for the beverage and food industry



### APPLICATIONS

Foodstuff industry, Milk processing industry, Other installations in the brewing, beverage and spirits industry

### DESCRIPTION

#### Further properties:

1 set consisting of 2 half shells, 4 screws and 4 nuts

For hoses with helix, use a reduced nozzle!

Material: stainless steel

No damage to lining through swaging process

Optimally adapted to PAGUFIX® nozzles due to the coordinated tooth geometry

Reusable

Rubber protection rings available in blue

Smooth and hygienically clean connection, without any transition between lining and fitting

Very high compression strength and resistance to pull-off forces, also with hot cleaning through ideal tooth geometry

### TECHNICAL DATA

nominal width	inner-Ø	wall thickness	outer-Ø clamping range	weight
Zoll/inch	mm	mm	mm	aprx. g/St
1/2	13	4,0	19-22	181
3/4	19	5,0	26-29	222
1	25	6,0	36-39	402
1 1/4	32	6,0	43-46	436
		8,0	47-50	464
1 1/2	38	6,5	50-52	521
		9,0	55-58	580
2	50	8,0	64-67	727
		10,0	69-71	814
2 1/2	63	7,5	74-78	1060
		12		
3	75	8,0	89-93	1349
		12,0	98-101	1648
4	100	9,0	116-122	2065
		15,0	128-132	2163

Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability

#### Industrial Fluid Solutions

ContiTech Schlauch GmbH  
Continentalstr. 3-5 | 34497 Korbach, Germany  
[industrial.hoses@fluid.contitech.de](mailto:industrial.hoses@fluid.contitech.de)

<https://industrial-hoses-partner.continental-industry.com>

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2024 ContiTech AG. All rights reserved. For complete information go to: <https://www.continental-industry.com/special-pages/disclaimer-publications>